

Protected Places Order

Table of Contents

1 Citation

2 Premises declared to be protected place

THE SCHEDULE

Legislative History

PROTECTED AREAS AND PROTECTED PLACES ACT (CHAPTER 256, SECTION 5(1))

PROTECTED PLACES ORDER

O 11

G.N. No. S 33/1997

REVISED EDITION 1998

(15th June 1998)

[31st January 1997]

Citation

- 1.** This Order may be cited as the Protected Places Order.

Premises declared to be protected place

- 2.** The premises described in the second column of the Schedule are hereby declared to be a protected place for the purposes of the Act, and no person shall be in those premises unless he is in possession of a pass-card or permit issued by the authority specified in the first column of the Schedule or has received the permission of an authorised officer on duty at the premises to enter the premises.

THE SCHEDULE

<i>First column</i>	<i>Second column</i>
The Authority	Protected Place
President of Singapore Technologies Electronics Limited	SINGAPORE TECHNOLOGIES ELECTRONICS LIMITED PREMISES

All that area comprised in part of Lot 12778 Mukim No. 18 (South Seletar), occupied by “SINGAPORE TECHNOLOGIES ELECTRONICS LIMITED PREMISES” containing an area of approximately 8,968 square metres and bounded approximately as follows:

Commencing at a point on the northern-most corner of the perimeter fence of the aforesaid “SINGAPORE TECHNOLOGIES ELECTRONICS LIMITED PREMISES” which point is 41,461.0 metres North and 29,864.1 metres East of the Survey Department origin of co-ordinates (N. 30,000 m, E. 30,000 m), the boundary runs along a line of fence on a bearing of approximately 184° 51’ for a distance of 63.0 metres and thence along successive lines of fence of bearings and distances approximately as under:

<i>Bearing</i>	<i>Distance in metres</i>
184° 23’	2.0
267° 31’	136.0
356° 59’	1.9
1° 30’	0.2
1° 30’	0.3 (along fence across a drain)
1° 30’	0.1 (along fence)
271° 12’	0.1 (along wall)
1° 12’	3.3
91° 12’	0.1
0° 51’	8.0 (along a gate)
270° 51’	0.1 (along wall)
0° 51’	0.2
0° 51’	0.2 (along wall across a drain)
0° 51’	2.9 (along wall)
90° 51’	0.1
0° 49’	20.0 (along fence)