

Protected Places (No. 6) Order 2001

Table of Contents

Enacting Formula

1 Citation and commencement

2 Premises declared to be protected place

THE SCHEDULE

No. S 240

PROTECTED AREAS AND PROTECTED PLACES ACT (CHAPTER 256)

PROTECTED PLACES (NO. 6) ORDER 2001

In exercise of the powers conferred by section 5(1) of the Protected Areas and Protected Places Act, the Minister for Home Affairs hereby makes the following Order:

Citation and commencement

1. This Order may be cited as the Protected Places (No. 6) Order 2001 and shall come into operation on 27th April 2001.

Premises declared to be protected place

2. The premises described in the second column of the Schedule are hereby declared to be a protected place for the purposes of the Act, and no person shall be in those premises unless he is in possession of a pass-card or permit issued by the authority specified in the first column of the Schedule or has received the permission of an authorised officer on duty at the premises to enter the premises.

THE SCHEDULE

First Column

Second Column

The Authority

Protected Place

Managing
of PowerGrid Ltd

Director 400 KV SUBSTATION AT AYER RAJAH CRESCENT, SINGAPORE.

All that area comprised in part of State Land Lots 3106C Mk 3 Pasir Panjang, occupied by “400 KV SUBSTATION AT AYER RAJAH CRESCENT, SINGAPORE” containing an area of about 11,529.1 square metres and bounded approximately as follows:

Commencing at the northeastern-most corner of the perimeter fence of the aforesaid “400 KV SUBSTATION AT AYER RAJAH CRESCENT, SINGAPORE” which the point is 31,106.6 metres North and 23,088.2 metres East of the Survey Department origin of co-ordinates, the boundaries run along successive lines of fence of bearings and distances approximately as under:

<i>Bearing</i>		<i>Distance in metres</i>
213° 21’	136.5	(along chain link fence)
303° 30’	33.3	(along chain link fence)
304° 31’	1.2	(along wall)
32° 51’	0.9	(along wall)
303° 16’	7.6	(across a gate)
214° 12’	0.9	(along wall)
303° 22’	10.8	(along wall)
216° 05’	0.2	(along wall)
305° 51’	0.3	(along wall)
303° 41’	25.9	(along chain link fence)
25° 10’	2.1	(along chain link fence)
16° 57’	2.1	(along chain link fence)
22° 46’	10.7	(along chain link fence)
23° 00’	1.2	(across a gate)
22° 59’	103.6	(along chain link fence)