

## **Protected Places (No. 3) Order 1996**

### **Table of Contents**

### **Enacting Formula**

**1**

**2**

### **THE SCHEDULE**

## **No. S 161**

### **PROTECTED AREAS AND PROTECTED PLACES ACT (CHAPTER 256)**

#### **PROTECTED PLACES (NO. 3) ORDER 1996**

In exercise of the powers conferred by section 5(1) of the Protected Areas and Protected Places Act, the Minister for Home Affairs hereby makes the following Order:

**1.** This Order may be cited as the Protected Places (No. 3) Order 1996 and shall come into operation on 12th April 1996.

**2.** The premises described in the second column of the Schedule are hereby declared to be a protected place for the purposes of the Protected Areas and Protected Places Act, and no person shall be in those premises unless he is in the possession of a pass-card or permit issued by the authority specified in the first column of that Schedule or has received the permission of an authorised officer on duty at the premises to enter the premises.

### **THE SCHEDULE**

First column

Second column

All that area comprised in part of state land lot 962 Mukim 31 (Changi) occupied by “TANAH MERAH COMPLEX” containing an area of about 59,997.1 square metres and bounded approximately as follows:

Commencing at the southwest corner of the perimeter fence of the aforesaid “TANAH MERAH COMPLEX” which point is 8,123.8 metres North and 13,313.7 metres East of the Survey Department origin of co-ordinates, the boundaries run along a line of fence on a bearing of approximately 45° 44' for a distance of 51.4 metres and thence along successive lines of fence and concrete high wall of bearings and distances approximately as under:

| Bearing  | Distance in metres                     |
|--|--|
| 48° 04'  | 60.0                                   |
| 90° 45'  | 46.9 (end of fence)                    |
| 125° 00'   | 11.0 (across open space)               |
| to the corner of high wall of the complex, thence its wall of bearing and distance approximately as under:   |  |
| 116° 14'   | 95.0 (along high wall)                 |
| to a corner of watch tower and along an arc distance of 5.9 metres along the wall subtended by an angle of 182° 48' and a radius of 1.8 metres to a corner of the watch tower, thence along its wall of bearings and distances approximately as under:   |  |
| 115° 43'   | 39.7 (across the gate and guard house) |
| 123° 31'   | 6.9 (across a drain)                   |
| to a corner of watch tower and along an arc distance of 2.7 metres along the wall subtended by an angle of 71° 46' and a radius of 2.1 metres to the corner of the watch tower, thence along its wall of bearing and distance approximately as under:  |  |
| 116° 17'   | 154.2 (along high wall)                |
| to a corner of watch tower and along an arc distance of 7.95 metres along the wall subtended by an angle 253° 12' and a radius of 1.8 metres to the corner of the watch tower, thence along its wall of bearing and distance approximately as under:   |  |
| 201° 28'   | 166.7 (along high wall)                |
| to a corner of watch tower and along an arc distance of 2.7 metres along the wall subtended by an angle of 83° 01' and a radius of 1.8 metres to the corner of the watch tower, thence along a distance of 3.5 metres and bearing of 198° 25' to a corner of fence of bearings and distances approximately as under: |  |