## GOVERNMENT NOTICES GOEWERMENTSKENNISGEWINGS

## SOUTH AFRICAN REVENUE SERVICE SUID-AFRIKAANSE INKOMSTEDIENS

No. R. 1334

12 December 2008

CUSTOMS AND EXCISE ACT, 1964. AMENDMENT OF SCHEDULE NO. 1 (No. 1/1/1367)

Under section 48 of the Customs and Excise Act, 1964, Part 1 of Schedule No. 1 to the said Act is hereby amended, with effect from 1 January 2009, to the extent set out in the Schedule hereto.

N NENE DEPUTY MINISTER OF FINANCE

SCHEDULE

By the substitution for the ADDITIONAL NOTES to CHAPTER 27 of the following:

ADDITIONAL NOTES:

1. Specifications:

In this Chapter the following expressions shall be deemed to refer to hydrocarbon fuels and oils which are liquid at normal temperature and pressure (20°C; one atmosphere) and which comply with all of the specifications hereunder assigned thereto or with any other specifications accepted or determined by the Commissioner (unless otherwise stated, the specification properties will be determined by the methods specified below) provided the intended uses of such fuels and oils are considered by the Commissioner in every case to be as specified hereunder in respect of such fuels and oils.

Methods to determine Specification Properties:

Distillation: ASTM D86/IP123 Density: ASTM D1298/4052 Knock Rating: ASTM D2700/IP236 Smoke Point: ASTM D1322/IP57 Sulphur Content: ASTM D2622/IP336 Kinematic Viscosity: ASTM D445/IP71 Cetane Number: ASTM D613/IP41 Cetane Index: ASTM D976

Note: ASTM means American Society for Testing of Materials, United States of America; IP means the Institute of Petroleum, United Kingdom

(a) "Aviation Spirit", being products intended for use, advertised for use, put up for use or otherwise marketed or disposed of for use as fuel in aircraft fitted with spark-ignition combustion piston engines

Distillation: 10 Per cent volume fraction evaporated below or at 75°C 40 Per cent volume fraction evaporated at or above 75°C 50 Per cent volume fraction evaporated below or at 105°C 90 Per cent volume fraction below or at 135°C Knock Rating: Minimum 100